

SIEMENS
mobile



Think in new possibilities

Wireless
Modules



Be inspired

Extremely compact and therefore ultra slim – our new GSM module TC35i opens new dimensions for applications in telemetry, telematics and telephony.

Think about new possibilities in

- Metering
- Fleet management and freight tracking
- Remote monitoring and voice applications
- Vending machines and POS terminals
- Security systems
- And much more for your planning

The TC35i is compatible with its predecessor engine TC35. As a truly optimized upgrade, it offers additional features such as the SIM application toolkit and extended AT commands for the industrial environment.

For contact and more information please visit www.siemens.com/wm

TC35i

pre-release

The ultra slim GSM module TC35i for boundless communication solutions

The new Dual-Band TC35i is designed for high-volume applications based on data, voice, SMS or fax. It allows easy integration into a wide range of applications, thanks to its minimized volume and its flexible and easy mounting concept using a ZIF connector and a GSC antenna plug. Thus the TC35i offers the user easy-to-integrate embedded wireless connectivity at low power consumption. As all Siemens modules it is R&TTE and GCF approved. It is also on the list of recommended modules of leading GSM network operators.



Wireless Modules Benefits and hard facts

Original size

General features:

- Dual-Band EGSM900 and GSM1800
- Compliant to GSM phase 2/2+
- Output power:
 - Class 4 (2 W) for EGSM900
 - Class 1 (1 W) for GSM1800
- Control via AT commands
- SIM Application Toolkit
- Multiplex RS232 interface
- Supply voltage range 3.3 ... 4.8 V
- Power save mode
- Power consumption:
 - Idle mode (registered) 25 mA
 - Speech mode 300 mA
 - Peak <2.5 A
 - Power down 50 μ A
 - Sleep mode 3.5 mA
- Dimensions: 54.5 x 36 x 3.6 mm
- Weight: 9 g
- Ambient temperature:
 - 20 °C ... +55 °C

Specifications for data transfer:

- CSD up to 14.4 kbps
- USSD
- Non transparent mode
- V.110
- 7E1-character framing

Specifications for SMS:

- Point-to-point MO and MT
- SMS cell broadcast
- Text and PDU mode

Specifications for fax:

- Group 3, class 1, 2

Specifications for audio:

- Half rate (HR)
- Full rate (FR)
- Enhanced full rate (EFR)
- Basic handsfree operation
 - Echo cancellation
 - Noise reduction

Additional features:

- Phone book
- Multiparty call
- Call diverting
- Real time clock
- Alarm management
- Several ringing tones
- DTMF (Dual Tone Multi Frequency)

Interfaces:

- 40-pin ZIF connector:
 - Power supply
 - SIM 3 V
 - RS232 bi-directional bus
 - Autobauding
 - Analog audio
- Antenna connector GSC, 50 Ω

More about Wireless Modules at:
www.siemens.com/wm

Copyright 2003, Siemens AG
Information and Communication
Mobile
Wireless Modules
Haidenauplatz 1
81667 Munich, Germany

Subject to changes in technology,
design and availability

Order No.:
A31001-W25-A201-X-7600
Printed in Germany